

Systemtemperaturen auswählen !

Vorlauf	75 °C
Rücklauf	65 °C
Raum	20 °C

Typ 21				
Nenn- bauhöhe mm	Länge mm	Leistung nach EN 442 W *	Exponent n -	Leistung W
1500	300	850	1,3218	850
	450	1.206	1,3184	1206
	600	1.563	1,3150	1563
1800	300	886	1,3192	886
	450	1.329	1,3192	1329
	600	1.772	1,3192	1772
	750	2.215	1,3192	2215
1950	300	936	1,3231	936
	450	1.405	1,3231	1405
	600	1.873	1,3231	1873
	750	2.341	1,3231	2341
2100	300	978	1,3327	978
	450	1.468	1,3327	1468
	600	1.957	1,3327	1957
	750	2.446	1,3327	2446

Typ 22				
Nenn- bauhöhe mm	Länge mm	Leistung nach EN 442 W	Exponent n -	Leistung W
1500	300	992	1,3038	992
	450	1.436	1,3140	1436
	600	1.880	1,3241	1880
1800	300	1.046	1,3387	1046
	450	1.569	1,3387	1569
	600	2.092	1,3387	2092
	750	2.615	1,3387	2615
1950	300	1.103	1,4255	1103
	450	1.654	1,4255	1654
	600	2.205	1,4255	2205
	750	2.756	1,4255	2756
2100	300	1.161	1,3343	1161
	450	1.742	1,3343	1742
	600	2.323	1,3343	2323
	750	2.903	1,3343	2903